

Print Date  
Jun-01-2015

Revision Date  
May-31-2015

Revision Number  
1

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**Product identifier**

Product code **GV111**  
Product name **Black**  
Product category **GV Series Gloss Vinyl Screen Ink**

**Other means of identification**

Synonyms None

**Recommended use of the chemical and restrictions on use**

Recommended use Printing operations

**Details of the supplier of the safety data sheet**

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: 1-913-422-1888	Stockport, England SK4 3EG
Tel: 1-800-677-4657	Tel: +44 161 442 2111
Fax: 1-913-422-2294	
<a href="http://www.nazdar.com">www.nazdar.com</a>	

**Emergency telephone number**

USA: Chemtrec: 1-800-424-9300  
Outside USA: Chemtrec: 1-703-527-3887  
24 Hour Emergency Phone Number

**2. HAZARDS IDENTIFICATION**

**Classification**

Serious eye damage/eye irritation	Category 2 - (H319)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Aspiration toxicity	Category 1 - (H304)

**Label elements**



**Signal Word**  
Danger

**Hazard Statements**

H304 - May be fatal if swallowed and enters airways  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation  
H351 - Suspected of causing cancer

**Precautionary Statements**

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P331 - Do NOT induce vomiting

**Hazards not otherwise classified (HNOC)**

May be harmful if swallowed. May be harmful in contact with skin. Combustible liquid.

**3. COMPOSITION/INFORMATION ON INGREDIENTS****Mixture**

Component	CAS-No	Weight %	Trade Secret	Note
Isophorone	78-59-1	30 - 60	*	
Naphtha (petroleum), heavy aromatic	64742-94-5	10 - 30	*	
Ethyl 3-Ethoxypropionate	763-69-9	5 - 10	*	
Carbon black	1333-86-4	1 - 5	*	
Petroleum naphtha, light aromatic	64742-95-6	1 - 5	*	
1,2,4-Trimethylbenzene (constituent)	95-63-6	1 - 5	*	1
Naphthalene (constituent)	91-20-3	< 1	*	1
1,3,5-Trimethylbenzene (constituent)	108-67-8	< 0.5	*	1
Cumene (constituent)	98-82-8	< 0.5	*	1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

**4. FIRST AID MEASURES****Description of first aid measures****General Advice**

Show this safety data sheet to the doctor in attendance.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

**Skin Contact**

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

**Inhalation**

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

**Ingestion**

DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

**Most important symptoms and effects, both acute and delayed**

None under normal use conditions.

**Indication of any immediate medical attention and special treatment needed****Notes to Physician**

Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.**Unsuitable Extinguishing Media**

No information available.

**Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

**Methods and material for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

**Conditions for safe storage, including any incompatibilities****Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

**Incompatible Products**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure limits**

Component	ACGIH TLV
Isophorone 78-59-1	Ceiling: 5 ppm
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> (inhalable fraction)
Naphthalene (constituent) 91-20-3	TWA: 10 ppm STEL: 15 ppm Skin
Cumene (constituent) 98-82-8	TWA: 50 ppm

Component	OSHA PEL
Isophorone 78-59-1	TWA: 4 ppm TWA: 23 mg/m <sup>3</sup> TWA: 25 ppm TWA: 140 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>
Naphthalene (constituent) 91-20-3	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm

	STEL: 75 mg/m <sup>3</sup>
Cumene (constituent) 98-82-8	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> Skin

Component	Ontario TWAEV
Isophorone 78-59-1	CEV: 5 ppm
Ethyl 3-Ethoxypropionate 763-69-9	TWA: 50 ppm TWA: 300 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>
Naphthalene (constituent) 91-20-3	TWA: 10 ppm STEL: 15 ppm Skin
Cumene (constituent) 98-82-8	TWA: 50 ppm

Component	Mexico OEL (TWA)
Isophorone 78-59-1	Peak: 5 ppm Peak: 25 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA/LMPE-PPT: 3.5 mg/m <sup>3</sup> STEL/LMPE-CT: 7 mg/m <sup>3</sup>
Naphthalene (constituent) 91-20-3	TWA/LMPE-PPT: 10 ppm TWA/LMPE-PPT: 50 mg/m <sup>3</sup> STEL/LMPE-CT: 15 ppm STEL/LMPE-CT: 75 mg/m <sup>3</sup>
Cumene (constituent) 98-82-8	TWA/LMPE-PPT: 50 ppm TWA/LMPE-PPT: 245 mg/m <sup>3</sup> STEL/LMPE-CT: 75 ppm STEL/LMPE-CT: 365 mg/m <sup>3</sup>

### Appropriate engineering controls

#### **Engineering Measures**

Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

### Individual protection measures, such as personal protective equipment

#### **Eye/face Protection**

Wear safety glasses with side shields (or goggles). If splashes are likely to occur. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Skin Protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

#### **Respiratory Protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

#### **General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical State</b>	Liquid	<b>Appearance</b>	Colored Liquid
<b>Odor</b>	Characteristic	<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH		No data available
Melting point/freezing point		No data available
Boiling point/Boiling Range	> 149 °C / 300 °F	
Flash Point	66 °C / 150 °F	Setaflash closed cup
Evaporation rate		No data available
Flammability Limit in Air		
Upper flammability limit		No data available
Lower flammability limit		No data available
Vapor Pressure		No data available
Vapor Density		No data available
Specific Gravity	1.03	
Water Solubility		No data available
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition Temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available
Explosive Properties	No data available	
Oxidizing Properties	No data available	

**Other Information**

Photochemically Reactive	Yes
Weight Per Gallon (lbs/gal)	8.61

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
66.25	67.62	5.71	684.5

**10. STABILITY AND REACTIVITY**

**Reactivity**

No information available.

**Chemical stability**

Stable under normal conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible materials**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

Inhalation	There is no data for this product.
Eye Contact	There is no data for this product.
Skin Contact	There is no data for this product.
Ingestion	There is no data for this product.

Component	Oral LD50
-----------	-----------

Isophorone 78-59-1	1870 mg/kg ( Rat )
Naphtha (petroleum), heavy aromatic 64742-94-5	>5000 mg/kg ( Rat )
Ethyl 3-Ethoxypropionate 763-69-9	3200 mg/kg ( Rat )
Carbon black 1333-86-4	>15400 mg/kg ( Rat )
Petroleum naphtha, light aromatic 64742-95-6	8400 mg/kg ( Rat )
1,2,4-Trimethylbenzene (constituent) 95-63-6	3400 mg/kg ( Rat )
Naphthalene (constituent) 91-20-3	490 mg/kg ( Rat )
1,3,5-Trimethylbenzene (constituent) 108-67-8	5000 mg/kg ( Rat )
Cumene (constituent) 98-82-8	1400 mg/kg ( Rat )

Component	LD50 Dermal
Isophorone 78-59-1	1390 mg/kg ( Rat )
Naphtha (petroleum), heavy aromatic 64742-94-5	>2000 mg/kg ( Rabbit )
Ethyl 3-Ethoxypropionate 763-69-9	10 mL/kg ( Rabbit )
Carbon black 1333-86-4	>3 g/kg ( Rabbit )
Petroleum naphtha, light aromatic 64742-95-6	>2000 mg/kg ( Rabbit )
1,2,4-Trimethylbenzene (constituent) 95-63-6	>3160 mg/kg ( Rabbit )
Naphthalene (constituent) 91-20-3	>2500 mg/kg ( Rat ) >20 g/kg ( Rabbit )
Cumene (constituent) 98-82-8	>3160 mg/kg ( Rabbit )

Component	Inhalation LC50
Isophorone 78-59-1	7 mg/L ( Rat ) 4 h
Naphtha (petroleum), heavy aromatic 64742-94-5	>590 mg/m <sup>3</sup> ( Rat ) 4 h
Petroleum naphtha, light aromatic 64742-95-6	3400 ppm ( Rat ) 4 h >5.2 mg/L ( Rat ) 4 h
1,2,4-Trimethylbenzene (constituent) 95-63-6	18 g/m <sup>3</sup> ( Rat ) 4 h
Naphthalene (constituent) 91-20-3	>340 mg/m <sup>3</sup> ( Rat ) 1 h
1,3,5-Trimethylbenzene (constituent) 108-67-8	24 g/m <sup>3</sup> ( Rat ) 4 h
Cumene (constituent) 98-82-8	39000 mg/m <sup>3</sup> ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** There is no data for this product.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** There is no data for this product.  
**Eye damage/irritation** There is no data for this product.  
**Irritation** There is no data for this product.  
**Corrosivity** There is no data for this product.  
**Sensitisation** There is no data for this product.  
**Mutagenic Effects** There is no data for this product.  
**Reproductive Effects** There is no data for this product.  
**STOT - single exposure** There is no data for this product.

**STOT - repeated exposure**  
**Chronic Toxicity**  
**Aspiration hazard**  
**Carcinogenicity**

There is no data for this product.  
 There is no data for this product.  
 There is no data for this product.  
 The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH
Isophorone 78-59-1	A3
Carbon black 1333-86-4	A3

Component	IARC
Carbon black 1333-86-4	Group 2B
Naphthalene (constituent) 91-20-3	Group 2B
Cumene (constituent) 98-82-8	Group 2B

Component	NTP
Naphthalene (constituent) 91-20-3	Reasonably Anticipated

Component	OSHA
Carbon black 1333-86-4	X
Naphthalene (constituent) 91-20-3	X
Cumene (constituent) 98-82-8	X

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	3,458.00 mg/kg
<b>ATEmix (dermal)</b>	2,481.00 mg/kg mg/l
<b>ATEmix (inhalation-dust/mist)</b>	15.00 mg/l

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Isophorone 78-59-1	96h EC50 Pseudokirchneriella subcapitata: 51.1 - 342 mg/L 72h EC50 Desmodesmus subspicatus: 475.4 mg/L
Naphthalene (constituent) 91-20-3	72h EC50 Skeletonema costatum: 0.4 mg/L
Cumene (constituent) 98-82-8	72h EC50 Pseudokirchneriella subcapitata: 2.6 mg/L

Component	Fish
Isophorone 78-59-1	96h LC50 Pimephales promelas: 132 - 159 mg/L [flow-through] 96h LC50 Lepomis macrochirus: 180 - 250 mg/L [static] 96h LC50 Pimephales promelas: 213 - 271 mg/L [static]
Ethyl 3-Ethoxypropionate 763-69-9	96h LC50 Pimephales promelas: 62 mg/L [static]
Petroleum naphtha, light aromatic 64742-95-6	96h LC50 Oncorhynchus mykiss: 9.22 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through]
Naphthalene (constituent)	96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L [static]

91-20-3	96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L [flow-through] 96h LC50 Oncorhynchus mykiss: 1.6 mg/L [flow-through] 96h LC50 Pimephales promelas: 1.99 mg/L [static] 96h LC50 Lepomis macrochirus: 31.0265 mg/L [static]
1,3,5-Trimethylbenzene (constituent) 108-67-8	96h LC50 Pimephales promelas: 3.48 mg/L
Cumene (constituent) 98-82-8	96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L [flow-through] 96h LC50 Oncorhynchus mykiss: 2.7 mg/L [semi-static] 96h LC50 Oncorhynchus mykiss: 4.8 mg/L [flow-through] 96h LC50 Poecilia reticulata: 5.1 mg/L [semi-static]

Component	Crustacea
Isophorone 78-59-1	48h EC50 Daphnia magna: 117 mg/L
Ethyl 3-Ethoxypropionate 763-69-9	48h EC50 Daphnia magna: 970 mg/L
Carbon black 1333-86-4	24h EC50 Daphnia magna: >5600 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: 6.14 mg/L
Naphthalene (constituent) 91-20-3	48h EC50 Daphnia magna: 1.09 - 3.4 mg/L [static] 48h EC50 Daphnia magna: 1.96 mg/L [Flow through] 48h LC50 Daphnia magna: 2.16 mg/L
1,3,5-Trimethylbenzene (constituent) 108-67-8	24h EC50 Daphnia magna: 50 mg/L
Cumene (constituent) 98-82-8	48h EC50 Daphnia magna: 7.9 - 14.1 mg/L [static] 48h EC50 Daphnia magna: 0.6 mg/L

**Persistence and Degradability**

No information available.

**Bioaccumulation**

No information available.

Component	Partition coefficient
Isophorone 78-59-1	1.66
Naphtha (petroleum), heavy aromatic 64742-94-5	4.5
Ethyl 3-Ethoxypropionate 763-69-9	1.35
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63
Naphthalene (constituent) 91-20-3	3.3
Cumene (constituent) 98-82-8	3.55

**Other adverse effects**

No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Waste Disposal Methods**

Contain and dispose of waste according to local regulations.

**Contaminated Packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

**DOT**

Proper Shipping Name

Not regulated

Printing Ink



**ICAO / IATA / IMDG / IMO**  
**Proper Shipping Name**

Not Regulated  
 Printing Ink

**15. REGULATORY INFORMATION**

**International Inventories**

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

**U.S. Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
1,2,4-Trimethylbenzene (constituent)	95-63-6	1 - 5	1.0
Naphthalene (constituent)	91-20-3	< 1	0.1

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Component	CAS-No	Weight %
Isophorone	78-59-1	30 - 60

**U.S. State Regulations**

Component	Massachusetts Right To Know
Isophorone 78-59-1	X
Carbon black 1333-86-4	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Naphthalene (constituent) 91-20-3	X
1,3,5-Trimethylbenzene (constituent) 108-67-8	X
Cumene (constituent) 98-82-8	X

Component	Minnesota Right To Know
Isophorone 78-59-1	X
Carbon black 1333-86-4	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Naphthalene (constituent) 91-20-3	X
Cumene (constituent) 98-82-8	X

Component	New Jersey Right To Know
Isophorone 78-59-1	X
Carbon black 1333-86-4	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Naphthalene (constituent)	X

91-20-3	
Cumene (constituent) 98-82-8	X

Component	Pennsylvania Right To Know
Isophorone 78-59-1	X
Carbon black 1333-86-4	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Naphthalene (constituent) 91-20-3	X
Cumene (constituent) 98-82-8	X

**California Prop. 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	California Prop. 65
Carbon black	Carcinogen
Naphthalene (constituent)	Carcinogen
Cumene (constituent)	Carcinogen

*This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product*

**Canada**

Component	NPRI - National Pollutant Release Inventory
Isophorone 78-59-1	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Naphtha (petroleum), heavy aromatic 64742-94-5	Part 5, Other Groups and Mixtures Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Ethyl 3-Ethoxypropionate 763-69-9	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Petroleum naphtha, light aromatic 64742-95-6	Part 5, Other Groups and Mixtures
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Naphthalene (constituent) 91-20-3	Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
1,3,5-Trimethylbenzene (constituent) 108-67-8	Part 5, Isomer Groups total of 1,2,3-Trimethylbenzene, CAS No. 526-73-8, and 1,3,5-Trimethylbenzene, CAS No. 108-67-8, except 1,2,4-Trimethylbenzene, CAS No. 95-63-6 Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Cumene (constituent) 98-82-8	Part 1, Group A Substance Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999

**16. OTHER INFORMATION**

<b>HMIS:</b>	<b>Health</b>	<b>Flammability</b>	<b>Reactivity</b>	<b>Personal Protection</b>
	2 *	2	0	X

**Key or legend to abbreviations and acronyms used in the safety data sheet**

**Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA TWA (time-weighted average)  
STEL STEL (Short Term Exposure Limit)  
Ceiling Maximum limit value

**ACGIH: (American Conference of Governmental Industrial Hygienists)**

A1 - Known Human Carcinogen  
A2 - Suspected Human Carcinogen  
A3 - Animal Carcinogen

**IARC: (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans  
Group 2A - Probably Carcinogenic to Humans  
Group 2B - Possibly Carcinogenic to Humans

**NTP: (National Toxicity Program)**

Known - Known Carcinogen  
Reasonably Anticipated to be a Human Carcinogen

**OSHA: (Occupational Safety & Health Administration)**

X - Present

**Revision Date** May-31-2015

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of MSDS**