

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

## 1 Identification

- **Product identifier**
- **Trade name:** R-BK1 Rolmark Black Stencil Ink
- **Article number:** 20887,20903,5A132,20928,20929,33564,4HY29
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Printing inks
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Marsh Shipping Supply Co.,LLC  
926 McDonough Lake Road - Unit E  
Collinsville, IL 62234  
USA
- **Information department:** customerservice@msscllc.com
- **Emergency telephone number:**  
Infotrac: 1-800-535-5053  
International; 352-323-3500 (CALL COLLECT)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Additional information:**

The pigment Carbon Black CAS# 1333-86-4, is suspected of causing cancer when inhaled as a dust form. This pigment is bound in the ink, and under normal conditions of use the exposure to the dust form is not likely.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS02, GHS07, GHS08
- **Signal word** Warning

- **Hazard-determining components of labeling:**

Carbon black

- **Hazard statements**

Flammable liquid and vapour.

Causes serious eye irritation.

Suspected of causing cancer.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

**Trade name: R-BK1 Rolmark Black Stencil Ink**

(Contd. of page 1)

Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Information pertaining to particular dangers for man and environment:**

· **Potential Chronic Health Effects**

Prolonged or repeated exposure of vapors, spray, or material may cause diseases of the lungs. Reports have associated repeated overexposure to solvents with brain and nervous system damage. Intentional misuse of this product may be harmful or fatal.

· **Target Organs**

Overexposure to this material or its components has been suggested as a cause of the following effects in laboratory animals and/or humans, and may aggravate preexisting disorders of these organs in humans: Anemia, Blood disorders, Brain damage, Cardiac function, eye, liver, lung, menstrual and fertility, skin, respiratory, Central Nervous System

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Hazardous components**

123-42-2	4-hydroxy-4-methylpentan-2-one	81.8%
	⚠ Flam. Liq. 3, H226; ⚠ Eye Irrit. 2, H319	

(Contd. on page 3)

# Safety Data Sheet


acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

**Trade name: R-BK1 Rolmark Black Stencil Ink**

(Contd. of page 2)

	Polymer of modified Rosin Resin	5.8%
1333-86-4	Carbon black  Carc. 2, H351	5.6%
112945-52-5	Amorphous Fumed Silica, Silicon Dioxide, Crystalline Free	2.8%

**Additional information:**

This product contains pigments which may become a dust nuisance when removed by abrasive blasting or sanding. Airborne nuisance particulates have an ACGIH TLV for total dust of 10mg/M3

## 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Take affected persons out into the fresh air.  
Involve doctor immediately.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water for 15 minutes. If irritation exists call physician.

· **After eye contact:**

Rinse opened eye for fifteen minutes under running water. If irritation persists, consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed**

Breathing difficulty

Headache

Dizziness

Thirst

Cramp

Gastric or intestinal disorders

Coughing

Allergic reactions

Nausea

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture**

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

USA

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

Trade name: **R-BK1 Rolmark Black Stencil Ink**

(Contd. of page 3)

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- **Precautions for safe handling**

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Handle with care. Avoid jolting, friction and impact.

Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing or moving, observe grounding/grounding of containers and other equipment when handling.

- **Information about protection against explosions and fires:** Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Prevent any seepage into the ground.

- **Information about storage in one common storage facility:**

Do not store together with oxidizing and acidic materials as well as heavy-metal compounds.

Store away from foodstuffs.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

Protect from exposure to the light.

- **Specific end use(s)** No further relevant information available.

USA

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

Trade name: R-BK1 Rolmark Black Stencil Ink

(Contd. of page 4)

## 8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

### 123-42-2 4-hydroxy-4-methylpentan-2-one

PEL Long-term value: 240 mg/m<sup>3</sup>, 50 ppm

REL Long-term value: 240 mg/m<sup>3</sup>, 50 ppm

TLV Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

### Polymer of modified Rosin Resin

PEL Long-term value: 15\* 5\*\* mg/m<sup>3</sup>  
\*Total Dust \*\*Respirable Fraction

### 1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m<sup>3</sup>

REL Long-term value: 3.5\* mg/m<sup>3</sup>  
\*0.1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV Long-term value: 3\* mg/m<sup>3</sup>  
\*inhalable fraction

### 112945-52-5 Amorphous Fumed Silica, Silicon Dioxide, Crystalline Free

TLV Long-term value: 3.5 mg/m<sup>3</sup>

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Do not eat, drink, smoke or sniff while working.

- **Breathing equipment:**

Use suitable respiratory protective device in case of insufficient ventilation.

Use only with adequate ventilation.

Do not breath vapors, spray mists, or sanding dusts. Use air purifying respirators fitted with organic vapor/HEPA cartridges only if air monitoring demonstrates solvent/particulate levels do not exceed the respirator maximum use concentration. Use properly fitted NIOSH approved respirators. Local and general exhaust should minimize any exposure.

- **Protection of hands:**



Protective gloves

- **Material of gloves**

Nitrile or natural rubber gloves are typically used to protect from minor contact. Butyl type are best for prolonged contact.

Nitrile rubber, NBR

(Contd. on page 6)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

Trade name: R-BK1 Rolmark Black Stencil Ink

(Contd. of page 5)

· **Eye protection:**

Vapor proof safety goggles or full face respirator

· **Body protection:**

Solvent resistant protective clothing

Impervious protective clothing

Tyvek(R) coveralls to protect from light overspray protection or Saranex 23-P(R) for moderate exposure.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

<b>Form:</b>	Fluid
<b>Color:</b>	Black
<b>Odor:</b>	Alcohol-like
<b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	150 °C (302 °F)

· **Flash point:** 58 °C (136 °F)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 620 °C (1148 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Not determined.· **Explosion limits:**

<b>Lower:</b>	1.4 Vol %
<b>Upper:</b>	8.1 Vol %

· **Vapor pressure at 20 °C (68 °F):** 1.1 hPa (1 mm Hg)· **Density at 20 °C (68 °F):** 0.9899 g/cm<sup>3</sup> (8.261 lbs/gal)· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

**Trade name: R-BK1 Rolmark Black Stencil Ink**

(Contd. of page 6)

<b>· Solvent content:</b>	
<b>Organic solvents:</b>	81.8 %
<b>VOC content:</b>	81.8 %
	809.7 g/l / 6.76 lb/gl
<b>· Solids content:</b>	
	18.2 %
<b>· Other information</b>	
	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with acids, alkalis and oxidizing agents.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
Nitrogen oxides  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	LD50	4000 mg/kg (rat)
Dermal	LD50	13630 mg/kg (rab)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**  
Sensitizing effect through inhalation is possible with prolonged exposure.  
Sensitizing effect by skin contact is possible with prolonged exposure.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
Danger through skin absorption.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1333-86-4	Carbon black	2B	5.6%
-----------	--------------	----	------

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

USA

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

Trade name: R-BK1 Rolmark Black Stencil Ink

(Contd. of page 7)

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
This statement was deduced from the properties of the single components.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.  
Hand over to hazardous waste disposers.  
This material and containers that are not empty, if discarded, would be regulated as a hazardous waste under RCRA. Treatment and disposal must be completed at a RCRA permitted treatment, storage, and disposal facility (TSD). The storage and transportation of RCRA hazardous wastes are also regulated by the USEPA.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>   | UN1210  |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul> | Printing ink<br>1210 Printing ink<br>PRINTING INK   |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>   | 3 Flammable liquids<br>Ink, not regulated by Title 49 Part 173.150 Exceptions for Class 3 (flammable) and combustible liquids, (f)(1) |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>  | 3   |



(Contd. on page 9)

USA



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

Trade name: R-BK1 Rolmark Black Stencil Ink

(Contd. of page 8)

· ADR, IMDG, IATA



· Class 3 Flammable liquids  
 · Label 3

· Packing group III  
 · DOT, ADR, IMDG, IATA

· Environmental hazards:  
 · Marine pollutant: No

· Special precautions for user Bulk packaging may be regulated / classified differently than non-bulk depending on mode of transport  
 Warning: Flammable liquids

· Danger code (Kemler): 30  
 · EMS Number: F-E,S-D

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR  
 · Excepted quantities (EQ) Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

· IMDG  
 · Limited quantities (LQ) 5L  
 · Excepted quantities (EQ) Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN1210, Printing ink, 3, III

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture  
 · TSCA (Toxic Substances Control Act):  
 All ingredients are listed or exempt.

123-42-2	4-hydroxy-4-methylpentan-2-one
1333-86-4	Carbon black
	acrylic copolymer -EU Polymer exempted- Not Regulated
112945-52-5	Amorphous Fumed Silica, Silicon Dioxide, Crystalline Free

· Proposition 65 /Chemicals known to cause cancer:

1333-86-4	Carbon black	5.6%
-----------	--------------	------

· Cancerogenity categories

· TLV (Threshold Limit Value established by ACGIH)

1333-86-4	Carbon black	A4	5.6%
-----------	--------------	----	------

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

Trade name: **R-BK1 Rolmark Black Stencil Ink**

(Contd. of page 9)

· <b>NIOSH (National Institute for Occupational Safety and Health)</b>			
123-42-2	4-hydroxy-4-methylpentan-2-one	Guidelines 89-104	81.8%
1333-86-4	Carbon black	*	5.6%

· **State regulations**

· <b>Massachusetts Right-to-know / Hazardous Substance Codes</b>			
123-42-2	4-hydroxy-4-methylpentan-2-one	2,4	81.8%
1333-86-4	Carbon black	2,4 F5	5.6%

· <b>Florida Hazardous / Toxic Substance Lists</b>			
123-42-2	4-hydroxy-4-methylpentan-2-one	Toxic	81.8%

· <b>Pennsylvania Hazardous Substances</b>			
123-42-2	4-hydroxy-4-methylpentan-2-one	--	81.8%

· <b>Minnesota Right To Know / Hazardous Substances</b>			
123-42-2	4-hydroxy-4-methylpentan-2-one	ANO	81.8%
1333-86-4	Carbon black	Codes: ANOR, Carcinogen	5.6%

· <b>Illinois Right To Know</b>			
None of the ingredients is listed.			

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms** GHS02, GHS07, GHS08· **Signal word** Warning· **Hazard-determining components of labeling:**

Carbon black

· **Hazard statements**

Flammable liquid and vapour.

Causes serious eye irritation.

Suspected of causing cancer.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**· **Occupational Safety and Health Act (OSHA)**

Immediate (acute) health hazard

(Contd. on page 11)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/18/2015

Reviewed on 06/17/2015

**Trade name: R-BK1 Rolmark Black Stencil Ink**

(Contd. of page 10)

*Delayed (chronic) Health Hazard*

- **Water hazard class:** *Water hazard class 1 (Self-assessment): slightly hazardous for water.*
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

### 16 Other information

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

· **Relevant phrases**

*H226 Flammable liquid and vapour.*

*H319 Causes serious eye irritation.*

*H351 Suspected of causing cancer.*

- **Contact:** *Compliance Department*

- **Date of preparation / last revision** *06/18/2015 / -*

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*Flam. Liq. 3: Flammable liquids, Hazard Category 3*

*Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A*

*Carc. 2: Carcinogenicity, Hazard Category 2*