

1. PRODUCT IDENTIFICATION

PRODUCT NAME: 94
PRODUCT COLOR: Reconditioner
RECOMMENDED USE:

Manufacturer/Supplier:

American Coding & Marking Ink Co., Inc.
1220 North Avenue
Plainfield, NJ 07062-1796

1-908-756-0373

USA

Emergency Telephone Number:

TRANSPORTATION: CHEMTREC : 1-800-424-9300 (North America)
1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION**Emergency Overview:****GHS Classification:**

Flammable liquids	Category 3
Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3

GHS label elements, including precautionary statements

Pictogram

Signal Word **Danger**

Hazard Statements

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H315	Causes skin irritation
H318	Causes serious eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking
P233	Keep container tightly closed
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash skin thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/protective clothing/eye protection/face protection
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P302+P352	IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310	Immediately call a POISON CENTER or doctor/physician
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P330	Rinse mouth
P332+P313	If skin irritation occurs: Get medical advice/attention
P362+P364	Take off contaminated clothing and wash it before reuse
P370+P378	In case of fire: Use Water spray, CO2, dry chemical, or alcohol resistant foam to extinguish
P403+P235	Store in a well-ventilated place. Keep cool
P501	Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
n-Butyl Alcohol	71-36-3	50-70
2-Butoxyethanol	111-76-2	20-40
4-Hydroxy-4-methyl-2-pentanone	123-42-2	20-40

4. FIRST AID MEASURES**First Aid Measures**

Ingestion: If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Eyes: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin: Remove contaminated clothing. Wash off with soap and plenty of water. Consult a physician.

Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Most important symptoms and effects**Symptoms**

Eye contact may result in redness, pain, blurred vision, burning sensation. Skin contact may result in irritation, defatting or dermatitis. Inhalation may cause drowsiness or dizziness. Inhalation may cause respiratory tract irritation. Ingestion may cause nausea, dizziness and headache.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically

5. FIREFIGHTING MEASURES**Suitable extinguishing media:**

Water fog, Multipurpose foam, Dry chemical, CO₂

Unsuitable extinguishing media:

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards in case of fire:

Fight as volatile liquid fire
Flashback fires may occur
Vapors are dense and may travel to remote ignition source

Hazardous combustion products:

Carbon oxides, organic combustion products which may be toxic and/or irritating

Protective equipment and precautions for fire fighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions:**

Wear chemical goggles, gloves, boots and protective clothing. Wear respirator if necessary. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition and heat.

Environmental precaution:

Prevent additional discharge of material. Prevent material from entering sewers or water courses.

Methods and materials for containment and cleaning up:

Absorb small spills with sand, filter-aid, vermiculite or other inert absorbent material, then place in a chemical waste container. For large spills, contain with sand or earth dikes. Dispose of waste in accordance with applicable government regulations.

7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid contact with eyes. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Unscrew all caps slowly. Do not unscrew entirely until all pressure has been completely released. Keep away from heat/sparks/open flames/hot surfaces. Emptied containers may retain residues. Precautions apply to emptied containers.

Conditions for safe storage, including incompatibilities:

Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep storage temperature between 4-32 °C (40-90 °F). Incompatible with strong oxidizing agents, strong acids, strong bases, alkali metals and halogens.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Guidelines:

Chemical Name and CAS#	ACGIH TLV	OSHA PEL	NIOSH IDLH
n-Butyl Alcohol 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m ³ skin
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ skin	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
4-Hydroxy-4-methyl-2-pentanone 123-42-2	TWA: 50 ppm	TWA: 50 ppm TWA: 240 mg/m ³	IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m ³

Appropriate engineering controls

Apply technical measures to comply with the occupational exposure limits. Local exhaust and mechanical ventilations are recommended to be used as engineering controls.

Individual protection measures, such as personal protective equipment:

Eye/Face protection: Safety glasses with side shields or chemical goggles must be worn.

Skin/Body protection: Wear protective gloves. Wear suitable protective clothing and footwear appropriate for the risk of exposure.

Respiratory protection: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

General hygiene: Handle in accordance with good industrial hygiene and safety practice.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

<u>Property</u>	<u>Values</u>	<u>Remarks-Methods</u>
Physical state:	Liquid	
Odor:	Moderate	
Odor threshold:	Not determined	
pH:	Not determined	
Melting point/freezing point:	Not determined	
Boiling point/Boiling range:	Not determined	
Flash point:	37.2 °C / 99 °F	Tag Closed Cup
Evaporation Rate:	<1	butyl acetate = 1
Flammability (solid, gas):	Not determined	
Upper/lower flammability limits:	Not determined	
Vapor pressure:	Not determined	
Vapor density:	>1	air = 1
Specific gravity:	0.86	water = 1
Water solubility:	Partially soluble	
Solubility in other solvents:	Not determined	
Partition Coefficient:	Not determined	
Auto-ignition Temperature:	Not determined	
Decomposition temperature:	Not determined	
Viscosity:	Not determined	
VOC Content (%):	100 %	
VOC Content:	7.2 lbs/gal	

10. STABILITY AND REACTIVITY**Reactivity:**

Not reactive under normal conditions.

Chemical Stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

None under normal processing.

Conditions to avoid:

Keep out of reach of children. Keep away from heat, sparks and open flame. Keep away from contact with incompatible materials.

Incompatible materials:

Strong oxidizing agents, strong acids, strong bases, alkali metals, halogens

Hazardous decomposition products:

Carbon oxides, thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Eye contact:** Causes serious eye damage**Skin contact:** Causes skin irritation

SAFETY DATA SHEET

SDS# 0094-09

Revision Date: 9/4/2018

Inhalation: May cause respiratory irritation. May cause drowsiness or dizziness.

Ingestion: Harmful if swallowed

Component Information:

Chemical Name and CAS#	Oral LD50	Dermal LD50	Inhalation LC50
n-Butyl Alcohol 71-36-3	= 790 mg/kg (Rat)	= 5,620 mg/kg (Rabbit)	>17.9 mg/l (Rat) 4 h
2-Butoxyethanol 111-76-2	= 1,300 mg/kg (Rat)	> 2,000 mg/kg (Guinea pig)	LC0 > 3.1 mg/L (Guinea pig) 1h
4-Hydroxy-4-methyl-2-pentanone 123-42-2	= 2,520 mg/kg (Rat)	= 13,500 mg/kg (Rabbit)	> 10 mg/L (Rat) 4 h

Information on physical, chemical and toxicological effects:

Symptoms Please see section 4 of this SDS for symptoms

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Carcinogenicity:

Chemical Name	ACGIH	IARC	NTP	OSHA
None				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Limited evidence of carcinogenicity

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity:

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Component Information

Chemical Name and CAS#	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
n-Butyl Alcohol 71-36-3	EC50 - Desmodesmus subspicatus - 500 mg/L - 72h	LC50 - Pimephales promelas - 1840 mg/L - 96 h	No data	EC50 - Daphnia magna - 1983 mg/L - 48 h
2-Butoxyethanol 111-76-2	EbC50 - Pseudokirchneriella subcapitata - 911 mg/L - 72h	LC50 - Oncorhynchus mykiss - 1,474 mg/L - 96h	No data	EC50 - Daphnia magna - 1,550 mg/L - 48h
4-Hydroxy-4-methyl-2-pentanone 123-42-2	No data	LC50 - Lepomis macrochirus - 420 mg/L - 96h	No data	EC50 - Daphnia magna - 9,000 mg/L - 24h

Persistence/Degradability:

Not determined

Bioaccumulation:

Not determined

Mobility:

Not determined

Other Adverse Effects:

No data available

13. DISPOSAL CONSIDERATIONS**Disposal of Wastes:**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging:

Dispose of as unused product in accordance with applicable regional, national and local laws and regulations.

SECTION 14 – TRANSPORTATION INFORMATION**DOT**

UN number 1210
 Proper shipping name PRINTING INK
 Hazard class 3
 Packing group III
 ERG# 129

IATA

UN number 1210
 Proper shipping name PRINTING INK
 Hazard class 3
 Packing group III

IMDG

UN number 1210
 Proper shipping name PRINTING INK
 Hazard class 3
 Packing group III
 Marine pollutant No

SECTION 15 – REGULATORY INFORMATION**TSCA STATUS:**

All Components listed

OTHER REGULATORY:

<u>Ingredient(s)</u>	<u>SARA 302</u>	<u>SARA 311/312</u>	<u>SARA 313</u>	<u>RECRA</u>	<u>CERCLA</u>
n-Butyl Alcohol	No	F, A	Yes	U031	No
2-Butoxyethanol	No	F, A, C	Yes	No	No
4-Hydroxy-4-methyl-2-pentanone	No	F, A, C	No	No	No

SARA 311/312 Codes:

R = Reactive Hazard
 P = Pressure Hazard
 F = Fire Hazard
 A = Immediate/Acute
 C = Delayed/Chronic

California Prop. 65 Components: Chemicals known to the state of California to cause birth defects or other reproductive harm:

This product does not contain any chemicals known to the state of California to cause cancer, birth defects or any other reproductive harm.

SECTION 16 – OTHER INFORMATION

HMIS:

Health:	2
Chronic Health Hazard	*
Flammability:	3
Reactivity:	0

Revision Date: 04-Sept-2018

Replaces: 15-Jun-2015

Revision Note: Review and update. Changes to sections 2, 11, 12, 15

Prepared by: Thomas Sweet, VP

DISCLAIMER OF LIABILITY

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material described in this MSDS. Information contained herein is given in good faith and believed to be true and accurate, but all statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material, or results to be obtained from the use thereof. All of the listed ingredients in this product that are considered to present a health hazard as defined in Appendix A of the OSHA "Hazard Communication" standard (29CFR 1910.1200) as listed in Section II. All of the information given, including ingredient identification, CAS Number, and quantity, is proprietary information, which has been provided in order to meet the objective of the "Hazard Communication" standard. Data provided here are typical and not intended for use as product specifications. This formulation information is confidential, and only to be disclosed in accordance with Federal and State safety and health regulations. Permission to disclose any ingredient information for any other purpose is neither given nor implied.