SAFETY DATA SHEET

Product Name: C-839 SILVER

General Use: Marking Ink

24 hr. Emergency Telephone Number

Infotrac 1-800-535-5053

Manufactured for:

Hitt Marking Devices, division of The Hitt Companies, Inc.

3231 W. MacArthur Blvd., Santa Ana, CA 92704

Phone: 1-847-395-1078 Website; www.HittMarking.com

WARNING: FLAMMABLE





Risk Statements: Irritating to eyes, respiratory system, throat and skin. Repeated exposure may cause skin dryness or cracking. Vapors may cause drowsiness and dizziness. Harmful if swallowed – can cause nausea, vomiting and narcosis.

<u>Safety Statements:</u> Avoid contact with skin and eyes. Keep container tightly closed. Keep away from sources of ignition. No smoking!

Potential Health Effects:

Acute: Moderate irritation of eyes, nose, throat and skin. Exposure to high concentrations may cause narcosis. Chronic: Repeated excessive exposure may cause lung, liver and kidney effects.

Emergency and First Aid Procedures:

INHALATION: Remove to fresh air, restore breathing. Treat symptoms. Consult a physician. Eyes: Flush immediately with water for 15 minutes. See a physician. Skin: Wash with soap and water. Remove contaminated clothing. Consult a physician if irritation persists. Ingestion: Drink water to dilute. Do not induce vomiting. Consult a physician or poison control center immediately.

SEE SECTIONS 8, 11 - The hazards are based on 100% of the contained materials. They may be reduced by their lower concentration.

		WEIGHT	
HAZARDOUS COMPONENTS	CAS NUMBER	PERCENT	
*N-BUTYL ALCOHOL	71-36-3	20	
DIACETONE ALCOHOL	123-42-2	10	
N-BUTOXYPROPANOL	5131-66-8	20	
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	15	
*ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	2	

INHALATION: REMOVE TO FRESH AIR, RESTORE BREATHING, TREAT SYMPTOMS, CONSULT A PHYSICIAN.

EYES: FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES. SEE A PHYSICIAN.

SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN IF IRRITATION PERSISTS. **INGESTION:** DRINK WATER TO DILUTE, DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

EXTINGUISHING MEDIA: ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT EXPLOSION WHEN EXPOSED TO EXTREME HEAT. FULL PROTECTIVE EQUIPMENT MAY BE NEEDED TO PROTECT FIREFIGHTERS FROM HAZARDOUS COMBUSTION PRODUCTS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: CLOSED CONTAINERS MAY EXPLODE OR COLLAPSE WHEN EXPOSED TO EXTREME HEAT. DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

839SLV SAFETY DATA SHEET PAGE 2 OF 3

STEPS TO TAKE IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE ALL SOURCES OF VAPOR IGNITION. VENTIALTE AREA. AVOID BREATHING VAPORS. REMOVE BY SUITABLE INERT ABSORBING MATERIAL.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP CONTAINERS CLOSED WHEN NOT IN USE, AND KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. AVOID EXCESSIVE INHALATION OF VAPOR OR MIST.

OTHER PRECAUTIONS

IN ACCORDANCE WITH GOOD INDUSTRIAL PRACTICE, HANDLE WITH CARE AND AVOID UNNECESSARY CONTACT. USE ONLY WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. FOR INDUSTRIAL USE ONLY. HMIS PERSONAL PROTECTIVE EQUIPMENT IS DEPENDENT UPON CONDITIONS OF USE.

	OCCUPATIONAL	EXPOSURE LIMITS
HAZARDOUS COMPONENTS	OSHA PEL	ACGIH TLV
*N-BUTYL ALCOHOL	50 PPM	50 PPM
DIACETONE ALCOHOL	50 PPM	50 PPM
N-BUTOXPROPANOL	N/A	N/A
PROPYLENE GLYCOL MONOMETHYL ETHER	N/A	100 PPM
*ETHYLENE GLYCOL MONOBUTYL ETHER	50 PPM	50 PPM

CONTROL MEASURES: GENERAL VENTILATION SHOULD BE SUFFICIENT FOR MOST CONDITIONS.

RESPIRATORY PROTECTION: WHEN USED WITH ADEQUATE VENTILATION, NONE NORMALLY REQUIRED. HOWEVER, WHEN REQUIRED, ITS USE MUST BE IN COMPLIANCE WITH ALL OSHA HEALTH AND FIT TESTING REQUIREMENTS, AS GIVEN IN 29CFR 1910.134.

PROTECTIVE CLOTHING: USE OF RUBBER OR PLASTIC GLOVES RECOMMENDED FOR PROLONGED OR REPEATED CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: USE PROTECTIVE CREAM WHEN SKIN CONTACT IS LIKELY.

EYE PROTECTION: SAFETY EYEWEAR SHOULD BE AVAILABLE TO AVOID ACCIDENTAL CONTACT

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, DRINKING OR SMOKING. NO SMOKING IN WORK AREA.

BOILING POINT: 243 to 698 DEG. F. SPECIFIC GRAVITY (H2O=1): 1.0

VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER

MATERIAL V. O. C.: 5.62 LB/GL (674G/L) **VAPOR PRESSURE:** 10.9 mm Hg @ 77 deg. F

SOLUBILITY IN WATER: INSOLUBLE

APPEARANCE AND ODOR: THIN LIQUID, ALCOHOLIC

FLASH POINT: 94 Deg. F METHOD USED: SETAFLASH

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 1.1% UPPER: 14.4%

STABILITY: STABLE CONDITIONS TO AVOID: HEAT, SPARKS AND OPEN FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID)

839SLV SAFETY DATA SHEET PAGE 3 OF 3

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY PRODUCE CARBON MONOXIDE. CARBON DIOXIDE AND OTHER HAZARDOUS DECOMPOSITION PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INDIVIDUAL INGREDIENT HAZARDS

*N-BUTYL ALCOHOL - INGESTION: LD50, 2,292 MG/KG - RAT. SKIN ABSORPTION: LD50, 3,430 MG/KG - RABBIT. INHALATION: LC50, 8,000 MG/KG, 1 HOUR - RAT (4 HOURS)

<u>DIACETONE ALCOHOL</u> - INGESTION: LD50, 4,000 MG/KG - RAT. SKIN ABSORPTION: LD50, 13,500 MG/KG. INHALATION: N/A

<u>N-BUTOXPROPANOL</u> - INGESTION: LD50, 3,300 MG/KG - RAT. SKIN ABSORPTION: LD50, 2,000 MG/KG - RAT. INHALATION: LC50, 3,300

MG/LITER.

PROPYLENE GLYCOL MONOMETHYL ETHER – INGESTION: LD50, 7,200 MG/KG – RAT. SKIN ABSORPTION: LD50, 13,000 MG/KG – RABBIT. INHALATION: LC50, 7,500 PPM – RAT (6 HOURS)

 $\frac{*\text{ETHYLENE GLYCOL MONOBUTYL ETHER}}{\text{INGESTION: LD50, 1,300 MG/KG}-\text{RAT.}} \cdot \text{SKIN ABSORPTION: LD50, 2,000 MG/KG} - \text{RAT.}$ $\frac{\text{INHALATION: N/A}}{\text{INHALATION: N/A}} \cdot \text{N/A}$

CARCINOGENICITY: NTP? NO? IARC MONOGRAPHIS? NO OSHA REGULATED? NO NONE CURRENTLY KNOWN.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

RESPIRATORY IRRITATION, DERMITITIS AND NAUSEA.

WASTE DISPOSAL METHOD: INCINERATION IS PERFERRED, IN COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. REFER TO SDS CAUTION INFORMATION BEFORE ATEMPTING CLEANUP.

DOT PROPER SHIPPING NAME: PRINTING INK

PACKING GROUP: II DOT HAZARD CLASS: 3

DOT UN/NA NUMBER: UN 1210

HAZARD SUBCLASS: N/A

EMERGENCY RESPONSE GUIDE NO. 26

THE LISTED TRANSPORTATION INFORMATION APPLIES ONLY TO GROUND TRANSPORT AND DOES NOT ADDRESS REGULATORY VARIATIONS DUE TO CHANGES IN PACKAGE SIZE, MODE OF SHIPMENT, OR OTHER REGULATORY DESCRIPTORS.

TOXIC SUBSTANCES CONTROL ACT: ALL OF THE INGREDIENTS ARE LISTED IN THE TSCA INVENTORY. SARA 313: *CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SEC. 313, ETC.

DISCLAIMER

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN WERE OBTAINED FROM SOURCES BELIEVED TO BE GENERALLY RELIABLE, BUT, WE MAKE NO WARRANTY CONCERNING THEIR ACCURACY OR SUFFICIENCY, AND WE WILL NOT BE HELD LIABLE FOR CLAIMS RELATING TO ANY PARTY'S USE OF OR RELIANCE ON INFORMATION OR RECOMMENDATIONS CONTAINED HEREIN.

DATE: 01/01/20 **HMIS CODES:** H-2, F-3, R-1, P-

LEGEND: NDA – No data available N/D - Not determined N/E – Not established