



The Portico™ system is available in a square corner or round corner frame that features ½" radius rounded corners and both come in a variety of colors and standard frame sizes. Both edge styles feature a 3/16" exposed edge.

Fabrication Note: Due to sign insert expansion and contraction, the insert should be .085" less than the sign frame's interior size. For example: an 8"x 8" frame insert would be: 7.915" x 7.915".

Features:

- » Frame material: high impact plastic (polymer)
- » Indoor and outdoor weatherable
- » Comes assembled with snap locks
- » Extra snap locks are available for purchase
- » Substrate thickness: 0-1/8" / 0-3.2 mm
- » Installation method: screws or tape (not included)
- » Sold individually

	Round Corner				Square Corner							10.0
Size	Black Sapphire	Slate Gray	Cocoa	Desert Sand	Linen White	Black Sapphire	Slate Gray	Cocoa	Desert Sand	Patriot Blue	Portabello	desk bar
2"x4" (51mmx102mm)	Χ	Х	Χ	Х	Х	Х	Χ	Х	Х			
2"x6" (51mmx152mm)	Χ	Х	Х	Х	Х	Х	Х	Х	Х			
2"x8" (51mmx203mm)	Χ	Х	Х	Х	Χ	Х	Х	Х	х	Х	Х	modular frame din
2"x8" (51mmx203mm) Desk Bar	Х	Х	Х	Х	Х	Х	Х	Х	Х			
2"x10" (51mmx254mm)	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Thoddia Itarrie dire
2"x10" (51mmx254mm) Desk Bar					Χ	Х	Х	Х	Х			
2"x12" (51mmx305mm)					Х	Х	Х	Х	Х			
3"x10" (76mmx254mm)	Χ	Х	Х	Х	Χ	Х	Х	Х	Х			
4"x4" (102mmx102mm)	Χ	Х	Х	Х	Χ	Х	Х	Х	Х	Х	Х	● ● ● ● ●
4"x8" (102mmx203mm)	Χ	Х	Х	Х	Χ	Х	Х	Х	Х	Х	Х	square round
4"x10" (102mmx254mm)	Χ	Х	Х	Х	Х	Х	Х	Х	Х			5/5/
6"x6" (152mmx152mm)	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	RESTROOM
6"x8" (152mmx203mm)	Χ	Х	Χ	Х	Х	Х	Х	Х	Х	Х	Х	LEVEL 3 - TERRACE
6"x10" (152mmx254mm)					Х	Х	Х	Х	Х			
6"x12" (152mmx305mm)	Х	Х	Х	Х	Х	Х	Х	Х	Х			
8"x8" (203mmx203mm)	Χ	Χ	Χ	Х	Х	Х	Х	Х	Х	Х	Х	
8.5"x11" (216mmx279mm)					Х	Х	Х	Х	Х			
10" x 10" (254mmx254mm)	Χ	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	
12" x 12" (305mmx305mm)	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	
Modular Frame Directory												Portico poly frame as a directory, using
3" x 18" (76mmx458mm) Header/ Base	Х	Х	Х	Х	Х	Х	Х	Х	Х			a directory, using multiple snap locks
2" x 18" (51mmx458mm) Insert Panels	Х	Χ	Х	Х	Х	Х	Х	Х	Х			T TI
Wall/Ceiling Mount Brack	et											
3" (76mm)	Х	Х	Х	Х	Х	Х	Х	Х	Х			

SNAP LECK TECHNOLOGY



Snap Lock Technology was developed to assist in easy sign face insertion, removal, and replacement.

The positive locking button snaps securely into the frame slot. Each snap lock has a pressure sensitive adhesive tab to hold the sign insert securely in place and provide tamper-resistant signage.

The combined technology of the Snap Lock and Portico poly frame is a designer's first choice for a reliable frame system.






Figure 1 - Snap Lock Technology profile view
Substrate






Figure 2 - Snap Lock Technology profile view, assembled







mounting

Traditionally, signs have been mounted directly to the wall using double sided tape. While this works, it is not an ideal solution in the long run when the signage needs to be updated, or a wall needs to be repainted. Portico Poly Frames simplify this by utilizing a keyhole mounting system for installing screws and drywall anchors.

Here's how it works:

The frame hangs by the keyholes on standard screws and drywall anchors, or whatever hardware is appropriate for your project. When it is time to replace or repaint around the sign, pull the sign insert out with a suction cup, loosen the screws and remove the frame from the wall.

Quick, easy, and the wall and signage stay in tact.

