Printing date 10/07/2015 Reviewed on 10/07/2015

1 Identification

· Product identifier

· Trade name: Rolmark Red Stencil Ink

· Article number: 20891, 20909, 1F152, 33566

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Printing inks

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Marsh Shipping Supply Co.,LLC 926 McDonough Lake Road - Unit E Collinsville, IL 62234

USA

· Information department: customerservice@msscllc.com

· Emergency telephone number:

Infotrac: 1-800-535-5053

International; 352-323-3500 (CALL COLLECT)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements

Flammable liquid and vapour.

Causes serious eye irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

(Contd. on page 2)

Printing date 10/07/2015 Reviewed on 10/07/2015

Trade name: Rolmark Red Stencil Ink

(Contd. of page 1)

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Information pertaining to particular dangers for man and environment:
- · Potential Chronic Health Effects

Prolonged or repeated exposure of vapors, spray, or material may cause diseases of the lungs. Reports have associated repeated overexposure to solvents with brain and nervous system damage. Intentional misuse of this product may be harmful or fatal.

· Target Organs

Overexposure to this material or its components has been suggested as a cause of the following effects in laboratory animals and/or humans, and may aggravate preexisting disorders of these organs in humans: Anemia, Blood disorders, Brain damage, Cardiac function, eye, liver, lung, menstrual and fertility, skin, respiratory, Central Nervous System

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Hazardous components				
123-42-2	4-hydroxy-4-methylpentan-2-one Trit. 2, H319	74.33%		
2425-85-6	1-(4-methyl-2-nitrophenylazo)-2-naphthol	9.4%		
37244-96-5	Nepheline Syenite	5.0%		
	Polymer of modified Rosin Resin	2.0%		
	Amorphous Fumed Silica, Silicon Dioxide, Crystalline Free	0.74%		
5468-75-7	Yellow AAOT Pigment 14	0.57%		

4 First-aid measures

- · Description of first aid measures
- · General information:

Take affected persons out into the fresh air.

Involve doctor immediately.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water for 15 minutes. If irritation exists call physcian.

(Contd. on page 3)

Printing date 10/07/2015 Reviewed on 10/07/2015

Trade name: Rolmark Red Stencil Ink

(Contd. of page 2)

· After eye contact:

Rinse opened eye for fifteen minutes under running water. If irritation persists, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Dizziness

Thirst

Cramp

Gastric or intestinal disorders

Coughing

Allergic reactions

Nausea

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Nitrogen oxides (NOx)

Carbon monoxide (CO)

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

USA

Printing date 10/07/2015 Reviewed on 10/07/2015

Trade name: Rolmark Red Stencil Ink

(Contd. of page 3)

7 Handling and storage

· Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Handle with care. Avoid jolting, friction and impact.

Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing or moving, observe grounding/grounding of containers and other equipment when handeling.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials as well as heavy-metal compounds.

Store away from foodstuffs.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

Protect from exposure to the light.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

	· Components	with limit	values tha	t require mo	nitoring at t	the workplace:
--	--------------	------------	------------	--------------	---------------	----------------

123-42-2 4-hydroxy-4-methylpentan-2-one

PEL Long-term value: 240 mg/m³, 50 ppm

REL Long-term value: 240 mg/m³, 50 ppm

TLV Long-term value: 238 mg/m³, 50 ppm

$2425\text{-}85\text{-}6\ 1\text{-}(4\text{-}methyl\text{-}2\text{-}nitrophenylazo)\text{-}2\text{-}naphthol$

TLV Long-term value: 10 (nuisance dust) mg/m³

37244-96-5 Nepheline Syenite

PEL Long-term value: 5*,10** mg/m³

*resipirable fraction, **inhalable fraction

Polymer of modified Rosin Resin

PEL Long-term value: 15* 5** mg/m³

*Total Dust **Respirable Fraction

112945-52-5 Amorphous Fumed Silica, Silicon Dioxide, Crystalline Free

TLV Long-term value: 3.5 mg/m³

5468-75-7 Yellow AAOT Pigment 14

TLV Short-term value: 10 as nuisance mg/m³

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Printing date 10/07/2015 Reviewed on 10/07/2015

Trade name: Rolmark Red Stencil Ink

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Do not eat, drink, smoke or sniff while working.

· Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

Do not breath vapors, spray mists, or sanding dusts. Use air purifying respirators fitted with organic vapor/HEPA cartridges only if air monitoring demonstrates solvent/particulate levels do not exceed the respirator maximum use concentration. Use properly fitted NIOSH approved respirators. Local and general exhaust should minimize any exposure.

· Protection of hands:



Protective gloves

· Material of gloves

Nitrile or natural rubber gloves are typically used to protect from minor contact. Butyl type are best for prolonged contact.

Nitrile rubber, NBR

· Eye protection:



Vapor proof safety goggles or full face respirator

· Body protection:

Solvent resistant protective clothing

Impervious protective clothing

Tyvek(R) coveralls to protect from light overspray protection or Saranex 23-P(R) for moderate exposure.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Color: Red
Odor: Alcohol-like
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 150 °C (302 °F)

(Contd. on page 6)

Printing date 10/07/2015 Reviewed on 10/07/2015

Trade name: Rolmark Red Stencil Ink

	(Contd. of pa
· Flash point:	58 °C (136 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	620 °C (1148 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	1.4 Vol %
Upper:	8.1 Vol %
· Vapor pressure at 20 °C (68 °F):	1.1 hPa (1 mm Hg)
Density at 20 °C (68 °F):	1.01764 g/cm³ (8.492 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	74.3 %
VOC content:	74.3 %
	756.4 g/l / 6.31 lb/gl
Solids content:	25.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Nitrogen oxides

Carbon monoxide and carbon dioxide

USA

Printing date 10/07/2015 Reviewed on 10/07/2015

Trade name: Rolmark Red Stencil Ink

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values tha	t are relevan	t for class	ification:
-----------	------------	---------------	-------------	------------

123-42-2 4-hydroxy-4-methylpentan-2-one

 Oral
 LD50
 4000 mg/kg (rat)

 Dermal
 LD50
 13630 mg/kg (rab)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitizing effect through inhalation is possible with prolonged exposure.

Sensitizing effect by skin contact is possible with prolonged exposure.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

Danger through skin absorption.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

2425-85-6 1-(4-methyl-2-nitrophenylazo)-2-naphthol

3 9.4%

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

This statement was deduced from the properties of the single components.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

(Contd. on page 8)

Printing date 10/07/2015 Reviewed on 10/07/2015

Trade name: Rolmark Red Stencil Ink

(Contd. of page 7)

- Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number DOT, ADR, IMDG, IATA	UN1210
UN proper shipping name DOT ADR	Printing ink 1210 Printing ink
IMDG, IATA	PRINTING INK
Transport hazard class(es)	
DOT	
Class Label	3 Flammable liquids 3
ADR, IMDG, IATA	2 El II II II
Class Label	3 Flammable liquids 3
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user Danger code (Kemler): EMS Number:	Warning: Flammable liquids 30 F-E,S-D
Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	
Transport/Additional information:	
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

Printing date 10/07/2015 Reviewed on 10/07/2015

Trade name: Rolmark Red Stencil Ink

(Contd. of page 8)

· UN "Model Regulation":

UN1210, Printing ink, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · TSCA (Toxic Substances Control Act):

All ingredients are listed or exempt.

123-42-2	4-hydroxy-4-methylpentan-2-one
2425-85-6	1-(4-methyl-2-nitrophenylazo)-2-naphthol
	acrylic copolymer -EU Polymer exempted- Not Regulated
	Nepheline Syenite
112945-52-5	Amorphous Fumed Silica, Silicon Dioxide, Crystalline Free
5468-75-7	Yellow AAOT Pigment 14

· Cancerogenity categories

· NIOSH (National Institute for Occupational Safety and Health)

123-42-2 4-hydroxy-4-methylpentan-2-one Guidelines 89-104 74.33%

· State regulations

· Massachussetts Right-to-know / Hazardous Substance Codes

123-42-2 4-hydroxy-4-methylpentan-2-one	2,4	74.33%
---	-----	--------

· Florida Hazardous / Toxic Substance Lists

123-42-2	4-hydroxy-4-methylpentan-2-one	Toxic	74.33%
----------	--------------------------------	-------	--------

· Pennsylvania Hazardous Substances

123-42-2 4-hydroxy-4-methylpentan-2-one 74.33%

· Minnesota Right To Know / Hazardous Substances

123-42-2	4-hydroxy-4-methylpentan-2-one	ANO	74.33%

· Illinois Right To Know

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements

Flammable liquid and vapour.

Causes serious eye irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

(Contd. on page 10)

Printing date 10/07/2015 Reviewed on 10/07/2015

Trade name: Rolmark Red Stencil Ink

(Contd. of page 9)

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Occupational Safety and Health Act (OSHA)

Immediate (acute) health hazard Delayed (chronic) Health Hazard

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

· Relevant phrases

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

- · Contact: Compliance Department
- · Date of preparation / last revision 10/07/2015 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

USA